



Features

- **Wide voltage range: 24V-26VAC/DC**
- **Integrated power unit**
- **Long-lived and maintenance-free by LED technology**
- **Fast Fixing Spring Connector**
- **On/off switch**
- **Magnet Fixing or Screw Fixing Type can be choose**

The lamp series LED 025-C-24 is suitable for all types of panels and enclosures, especially where space is at a premium. The lamps have a very long service life thanks to the use of LED technology.

Technical Data

LED 025-C-24	
Power consumption	max. 4W
Luminosity	400Lm at 120° (1,200Lm at 360° or equivalent 95W light bulb)
Lamp type	LED, angle of radiation 120° light color: daylight, color temperature: 6,000K to 7,000K
Service life	60,000h at +20°C (+68°F)
Connection	Fast Fixing Spring Connector
Mounting	magnet fixing or screw fixing (M5), torque 2Nm max.
Casing	plastic, transparent
Dimensions	see drawings
Weight	0.2kg
Operating/Storage temperature	-30 to +60°C (-22 to +140°F) / -40 to +85°C (-40 to +185°F)
Operating/Storage humidity	max. 90% RH (non-condensing)
Protection type/Protection class	IP20 / II (double insulated)

Mounting options: The lamps are available with magnet fixing for easy positioning in any steel cabinet or enclosure. A classic is the LED 025-C-24 with screw fixing.

Note: The lamp must not be used for household lighting.

Art. No.	Fixing type	Switch	Operating voltage
CCL5-M24	Magnet fixing	on/off light switch	24-26VAC/DC(min. 24V, max. 26V)
CCL5-S24	Screw fixing	on/off light switch	24-26VAC/DC(min. 24V, max. 26V)

¹ approx. 5 min. fixed switch-on duration

Dimensions

