



Technical Data

Range of product
Product or component type
Poles Compatibility
Fuse Size
Rated supply voltage
Rated operational current
Rated Insulation voltage
Rating current of fuse cartridge
Endurance
Fuse Type
Visual Status

Cx9 Series
Fuse Carrier
1P
10 x 38mm
230...240 V AC 50/60 Hz
32A @ 400V AC
690V AC
2/4/6/8/10/12/16/20/25/32 A
4000 (Number of mechanical operations)
aM, gG
With LED indication

Dimensions

Height
Width
Depth
Mounting support
Net weight
Device mounting
Connections - terminals
Tightening torque
Quantity per box

78mm
17.5mm
60mm
35 mm symmetrical DIN rail
0.044kg
Vertical (tolerance: +/- 23°)
Screw clamp terminals 1 cable(s) 1...16 mm²rigid
Screw clamp terminals 2 cable(s) 1...6 mm²rigid
Screw clamp terminals 1 cable(s) 1...16 mm²flexible with or without
Screw clamp terminals 2 cable(s) 1...6 mm²flexible with or without
2.2 N.m - with screwdriver flat Ø 5.5 mm
10

Environment

Protective treatment
Ambient air temperature for storage
Ambient air temperature for operation
Operating altitude
IP degree of protection
Pollution degree
Standards

TH
-40...70°C
-25...70°C
0...1800 m
IP20 conforming to IEC 60529
3
EN/IEC 60947-3
EN/IEC 60269