



Technical Data

Range of product	Cx9 Series
Product or component type	Fuse Carrier
Poles Compatibility	1P
Fuse Size	10 x 38mm
Rated supply voltage	230...240 V AC 50/60 Hz
Rated operational current	32A @ 400V AC
Rated Insulation voltage	690V AC
Rating current of fuse cartridge	2/4/6/8/10/12/16/20/25/32 A
Endurance	4000 (Number of mechanical operations)
Fuse Type	aM, gG
Visual Status	With LED indication

Dimensions

Height	78mm
Width	17.5mm
Depth	60mm
Mounting support	35 mm symmetrical DIN rail
Net weight	0.044kg
Device mounting	Vertical (tolerance: +/- 23°)
Connections - terminals	Screw clamp terminals 1 cable(s) 1...16 mm ² rigid Screw clamp terminals 2 cable(s) 1...6 mm ² rigid Screw clamp terminals 1 cable(s) 1...16 mm ² flexible with or without Screw clamp terminals 2 cable(s) 1...6 mm ² flexible with or without
Tightening torque	2.2 N.m - with screwdriver flat Ø 5.5 mm
Quantity per box	10

Environment

Protective treatment	TH
Ambient air temperature for storage	-40...70°C
Ambient air temperature for operation	-25...70°C
Operating altitude	0...1800 m
IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	3
Standards	EN/IEC 60947-3 EN/IEC 60269